




Adaptador Bridado

Flange Grooved



Recubrimiento: 1.Epóxico.
2.Pintura.
3.Galvanizado.

TAMAÑO NOMINAL MM/in	DIÁMETRO EXTERIOR MM/in	PRESIÓN DE TRABAJO PSI/ M/PA	DIMENSIONES MM/in		
			Do	L	n-Ø
NOMINAL SIZE MM/in	PIPE O.D. MM/in	WORKING PRESSURE PSI/ M/PA	DIMENSIONS MM/in		
			Do	L	n-Ø
50 2	60.3 2.375	300 2.07	121 4.76	20 0.787	4-Ø18 0.157-Ø0.709
65 2.5	73 2.875	300 2.07	140 5.511	20 0.787	4-Ø18 0.157-Ø0.709
80 3	88.9 3.5	300 2.07	152 5.984	20 0.787	4-Ø18 0.315-Ø0.709
100 4	114.3 4.5	300 2.07	191 7.52	21 0.827	8-Ø18 0.315-Ø0.709
125 5	141.3 5.563	300 2.07	216 8.5	21 0.827	8-Ø22 0.315-Ø0.866
150 6	168.3 6.626	300 2.07	241.3 9.5	21 0.827	8-Ø22 0.315-Ø0.866
200 8	219.1 8.626	300 2.07	298.5 11.75	24 0.945	8-Ø22 0.315-Ø0.866