




Cople Flexible

Flexible Coupling



Recubrimiento: 1.Epóxico.
2.Pintura.
3.Galvanizado.

TAMAÑO NOMINAL MM/iN	DIÁMETRO EXTERIOR MM/iN	PRESIÓN DE TRABAJO PSI/ M/PA	DIMENSIONES MM/iN			TAMAÑO DE TORNILLO
			A MM/iN	B MM/iN	C MM/iN	
NOMINAL SIZE MM/iN	PIPE O.D. MM/iN	WORKING PRESSURE PSI/ M/PA	DIMENSIONS MM/iN			BOLT SIZE
			A MM/iN	B MM/iN	C MM/iN	
25 1	33.7 1.327	300 2.07	55 2.165	95 3.74	45 1.772	2-M10*45
32 1 1/4	42.4 1.669	300 2.07	65 2.559	105 4.133	45 1.772	2-M10*45
40 1 1/2	48.3 1.900	300 2.07	71 2.795	110 4.331	45 1.772	2-M10*45
50 2	60.3 2.375	300 2.07	82 3.228	124 4.882	45 1.772	2-M10*55
65 2 1/2	73.0 2.875	300 2.07	98 3.858	141 5.551	45 1.772	2-M10*55
65 3OD	76.1 3.000	300 2.07	100 3.937	142 5.59	45 1.772	2-M10*55
80 3	88.9 3.500	300 2.07	113 4.449	160 6.299	46 1.811	2-M12*60
100 4	114.3 4.500	300 2.07	142 5.59	190 7.48	49 1.929	2-M12*65
125 5.5OD	139.7 5.500	300 2.07	168 6.614	218 8.583	49 1.929	2-M12*75
150 6.5OD	165.1 6.500	300 2.07	194 7.638	244 9.606	49 1.929	2-M12*75
150 6	168.3 6.625	300 2.07	198 7.795	248 9.764	49 1.929	2-M12*75
200 8	219.1 8.625	300 2.07	256 10.079	320 12.598	60 2.362	2-M16*100
250 10	273 10.748	300 2.07	328 12.913	420 16.535	64 2.52	2-M22*130
300 12	323.9 12.752	300 2.07	380 14.961	454 17.874	64 2.52	2-M22*130