



Salida Soldable Roscada

Welding Outlet Threaded

Medida mm/in	Rango in	Diametro Externo A mm/in	Longitud B mm/in	C mm/in	M mm/in	PESO Kgs/Lbs
Outlet Size mm/in	Header Size Range in	Outlet OD A mm/in	Outlet Length B mm/in	C mm/in	M mm/in	Weight Kgs/Lbs
8	Flat	19.1	31.8	10.7	18.0	0.05
0.25		0.750	1.250	0.421	0.789	0.11
15	1-1/2-2	27.8	25.4	23.1	12.7	0.08
0.5	2-2-1/2	1.094	1.000	0.91	0.500	0.17
20	2-1/2-8	34.9	28.6	22.9	12.7	0.12
0.75	1-1/4-1-1/2	1.375	1.125	0.900	0.500	0.26
25	1-1/2-2	39.5	28.60	34.4	12.7	0.13
1	2-2-1/2	1.555	1.126	1.354	0.500	0.29
32	2-1/2-3	47.5	31.8	44.0	12.7	0.19
1.25	3-4	1.870	1.252	1.732	0.500	0.42
40	5-8	55.0	31.8	49.8	22.2	0.22
1.5	1-1/2	2.165	1.252	1.961	0.875	0.47
50	2	69.3	38.1	61.8	22.2	0.38
2	2.5	2.728	1.500	2.433	0.875	0.57
65	3	80.4	54.0	62.7	28.6	0.55
2.5	4	3.165	2.215	2.469	1.125	1.15
(73.00D)	5					
	6					
	8					
65	2.5	83.5	54.0	62.7	28.6	0.55
2.5	3	3.290	2.215	2.469	1.125	1.15
(76.10D)	4					
	5					
	6					
80	3	98.0	63.5	77.9	38.1	0.77
3	4	3.861	2.500	3.068	1.500	1.70
	5					
	6					
	8					
100	4	125.2	76.2	102.3	50.8	1.32
	5	4.933	3.000	4.026	2.000	2.80
	6					
	8					